

MAAG 825BDS

GENSET

Standby Power	kVA	825
	kW	660
Prime Power	kVA	750
	kW	600
Soundproof canopy [mm]	W x L x H	1800x4500x2980
Open version [mm]	W x L x H	1800x4290x2360
Fuel tank [liter] -base	diesel	1140
Net total weight with canopy*	kg	7 800
Net total weight open version*	kg	7 000
Noise [in canopy design]	dB(A)	71
Control panel		MGD 500L MK2

* Including lubrication oil and coolant fluid, excluding fuel

[Info] Genset characteristics:

Displays:

Phase currents (A), Phase voltages (V), Line voltages, Integrated frequency and speed display.

Cooling water temperature, operating hours counter, oil pressure indicator.

[Info] AMF Genset control:

Standard voltage-free indications: genset running, high water temperature, low oil pressure, low battery voltage.



[Info] Prime power:

Prime Power is the maximum power accessible at the variable load for an unlimited number of hours per year in a variable load setting. It is not advisable that the variable load exceed 70% average of the prime power rating during any operational period. If the engine is running at 100% prime power, yearly hours should not exceed 500. Overload situations should be avoided however a 10% overload capability is available for a 1 hour period within a 12 hour cycle of operation.

[Info] Standby power:

Standby Rating for a standby engine should be sized for a maximum of 70% average load factor and roughly 500 hours per year. Standby power ratings should never be applied except in true emergency outage situations. With standby rated generators there is no overload capability built into the units.



MOTOR

Manufacturer		BAUDOIN
Model		6M33G825/5
Number of cylinders		6 in Line
Cycle		4
Aspiration		Turbocharger - intercooler
Cooling system		Water
Cooling circuit capacity	liter	159
Oil capacity	liter	61
Injection		direct
Speed/Frequency	rpm/Hz	1500/50
Fuel consumption	100%	182
	50%	91

ALTERNATOR

Manufacturer		STAMFORD
Number of Phase		3
Power factor		cos φ 0,8
Frequency [Hz]		50
Output voltage [VAC]		230 / 400 V
Protection		IP 23
Connection type		Star
Standby power	[kVA]	860
Insulation class		Class H

OTHER INFO

web: www.maaggenerator.com

CERTIFICATE

MARTON Szakértő Kft. Zrt.
 8500 Pétervárad, Andrássy út 11. sz. 11. emelet
 5040-10000000

Levegőtér: Kft.
 Regisztrációs szám: 11-11-11111111-11111111-11111111
 Operatív kód: 11-11-11111111-11111111-11111111

Levegőtér és környezetvédelmi minőségügyi tanúsítvány a levegőtér
 11111111

Tulajdonos és gyártó: Levegőtér és környezetvédelmi minőségügyi tanúsítvány a levegőtér
 11111111

Regisztrációs kód: 11111111-11111111-11111111
 Levegőtér és környezetvédelmi minőségügyi tanúsítvány a levegőtér
 11111111

COLEGES SUTTE
 11111111-11111111-11111111
 11111111-11111111-11111111

11111111-11111111-11111111
 11111111-11111111-11111111

CERTIFICATE

A RIKAJON Szakértő Iroda Kft.
 1048 Budapest, Andrássy út 12.
 1490-10000000

Levegőtér: Kft.
 Regisztrációs szám: 11-11-11111111-11111111-11111111
 Operatív kód: 11-11-11111111-11111111-11111111

Levegőtér és környezetvédelmi minőségügyi tanúsítvány a levegőtér
 11111111

Tulajdonos és gyártó: Levegőtér és környezetvédelmi minőségügyi tanúsítvány a levegőtér
 11111111

Regisztrációs kód: 11111111-11111111-11111111
 Levegőtér és környezetvédelmi minőségügyi tanúsítvány a levegőtér
 11111111

COLEGES SUTTE
 11111111-11111111-11111111
 11111111-11111111-11111111

11111111-11111111-11111111
 11111111-11111111-11111111



All of our products are made in Hungary in our own factory. Please kindly be notified that We reserve the right to make changes without the prior consent of the buyer except the standby and prime power which are always guaranteed. Thank you for understanding.
 All pictures shown here are for illustration purpose only.

MSZ EN ISO 14001:2015, MSZ EN ISO 9001:2015

