

## MAAG 440IVMG

### GENSET

Standby Power	kVA	440
	kW	352
Prime Power	kVA	400
	kW	320
Soundproof canopy [mm]	W x L x H	1400x3705x2400
Open version [mm]	W x L x H	1400x3450x1885
Fuel tank [liter] -base	diesel	880
Net total weight with canopy*	kg	4 500
Net total weight open version*	kg	4 100
Noise [in canopy design]	dB(A)	71
Control panel		MGD 500L MK2

\* Including lubrication oil and coolant fluid, excluding fuel

#### [Info] Genset characteristics:

Displays:

Phase currents (A), Phase voltages (V), Line voltages, Integrated frequency and speed display.

Cooling water temperature, operating hours counter, oil pressure indicator.

#### [Info] AMF Genset control:

Standard voltage-free indications: genset running, high water temperature, low oil pressure, low battery voltage.



#### [Info] Prime power:

**Prime Power** is the maximum power accessible at the variable load for an unlimited number of hours per year in a variable load setting. It is not advisable that the variable load exceed 70% average of the prime power rating during any operational period. If the engine is running at 100% prime power, yearly hours should not exceed 500. Overload situations should be avoided however a 10% overload capability is available for a 1 hour period within a 12 hour cycle of operation.

#### [Info] Standby power:

**Standby Rating** for a standby engine should be sized for a maximum of 70% average load factor and roughly 500 hours per year. Standby power ratings should never be applied except in true emergency outage situations. With standby rated generators there is no overload capability built into the units.



### MOTOR

Manufacturer		FPT IVECO
Model		CURSOR13TE3A.S551
Number of cylinders		6 in Line
Cycle		4
Aspiration		Turbocharger - aftercooler
Cooling system		Water
Cooling circuit capacity	liter	68
Oil capacity	liter	35
Injection		direct
Speed/Frequency	rpm/Hz	1500/50
Fuel consumption	100%	86
	50%	43

### ALTERNATOR

Manufacturer		MAAG
Number of Phase		3
Power factor		cos φ 0,8
Frequency [Hz]		50
Output voltage [VAC]		230 / 400 V
Protection		IP 23
Connection type		Star
Standby power	[kVA]	440
Insulation class		Class H

### OTHER INFO

web: [www.maaggenerator.com](http://www.maaggenerator.com)

#### CERTIFICATE

MARTON Szakértő Kft.  
 8520 Balatonudvari, Andrássy út 11. sz. 10. em.  
 8520 Balatonudvari

Levegő Kft.  
 Rákosmenti út 11. 1123 Budapest, Magyarország  
 Operatív Iktatás: 11 8715 Budapest, Magyarország  
 1123 Budapest

Legyenek meg a következők:  
 - a gyártóval szembeni jogok fenntartása a gyártóval szemben  
 - a gyártóval szembeni jogok fenntartása a gyártóval szemben  
 - a gyártóval szembeni jogok fenntartása a gyártóval szemben

COAGLES SZÉK  
 HUNGÁRIA  
 SZÉK: 1123 Budapest, Magyarország  
 HUNGÁRIA

MAAG Szakértő Kft.  
 8520 Balatonudvari, Andrássy út 11. sz. 10. em.  
 8520 Balatonudvari

#### CERTIFICATE

A RÁKOSMENTI Levegő Kft.  
 1123 Budapest, Andrássy út 11. sz. 10. em.  
 1123 Budapest, Magyarország

Levegő Kft.  
 Rákosmenti út 11. 1123 Budapest, Magyarország  
 Operatív Iktatás: 11 8715 Budapest, Magyarország  
 1123 Budapest

Legyenek meg a következők:  
 - a gyártóval szembeni jogok fenntartása a gyártóval szemben  
 - a gyártóval szembeni jogok fenntartása a gyártóval szemben  
 - a gyártóval szembeni jogok fenntartása a gyártóval szemben

COAGLES SZÉK  
 HUNGÁRIA  
 SZÉK: 1123 Budapest, Magyarország  
 HUNGÁRIA

MAAG Szakértő Kft.  
 8520 Balatonudvari, Andrássy út 11. sz. 10. em.  
 8520 Balatonudvari



All of our products are made in Hungary in our own factory. Please kindly be notified that We reserve the right to make changes without the prior consent of the buyer except the standby and prime power which are always guaranteed. Thank you for understanding.  
 All pictures shown here are for illustration purpose only.

MSZ EN ISO 14001:2015, MSZ EN ISO 9001:2015

