THE HUNGARIAN GENERATOR



MAAG 50MS

GENSET

| Standby Power | kVA | 50 |
|--------------------------------|--------|----------------|
| | kW | 40 |
| Prime Power | kVA | 45 |
| | kW | 36 |
| Soundproof canopy [mm] | WxLxH | 1000x2450x1680 |
| Open version [mm] | WxLxH | 1000x1900x1420 |
| Fuel tank [liter] -base | diesel | 101 |
| Net total weight with canopy* | kg | 1 030 |
| Net total weight open version* | kg | 850 |
| Noise [in canopy design] | dB(A) | 71 |
| Control panel | | MGD 500L MK2 |

^{*} Including lubrication oil and coolant fluid, excluding fuel

Info Genset characteristics:

Displays:

Phase currents (A), Phase voltages (V), Line voltages, Integrated frequency and speed display.

Cooling water temperature, operating hours counter, oil pressure indicator.

Info AMF Genset control:

Standard voltage-free indications: genset running, high water temperature, low oil pressure, low battery voltage.



ALTERNATOR

| | STAMFORD | | | |
|-------|------------------|--|--|--|
| | 3 | | | |
| | cos φ 0,8 | | | |
| | 50 | | | |
| | 230 / 400 V | | | |
| | IP 23 | | | |
| | Star | | | |
| [kVA] | 49,5 | | | |
| | Class H | | | |
| | [kVA] | | | |

OTHER INFO

web: www.maaggenerator.com



Info Prime power:

Prime Power is the maximum power accessible at the variable load for an unlimited number of hours per year in a variable load setting. It is not advisable that the variable load exceed 70% average of the prime power rating during any operational period. If the engine is running at 100% prime power, yearly hours should not exceed 500. Overload situations should be avoided however a 10% overload capability is available for a 1 hour period within a 12 hour cycle of operation.

Info Standby power:

Standby Rating for a standby engine should be sized for a maximum of 70% average load factor and roughly 500 hours per year. Standby power ratings should never be applied except in true emergency outage situations. With standby rated generators there is no overload capability built into the units.

MOTOR

| Manufacturer | | MAAG |
|--------------------------|--------|-----------|
| Model | | Y4105D |
| Number of cylinders | | 4 in Line |
| Cycle | | 4 |
| Aspiration | | Natural |
| Cooling system | | Water |
| Cooling circuit capacity | liter | 15,1 |
| Oil capacity | liter | 13 |
| Injection | | direct |
| Speed/Frequency | rpm/Hz | 1500/50 |
| Fuel consumption | 100% | 9 |
| | 50% | 6 |











